

BAND-N-GO Inc.

Banding Together with Industry



INDEX	Page
Stainless Steel Banding	2, 3, 4
Stainless Buckles & Brackets.....	5
Stainless Steel Seals.....	6
Pre-Cut Straps.....	7
SS Banding Tools	8, 9
Stainless Steel Cable Ties	10, 11
SS Cable Tie Tools	12
Pre-Formed Clamps	13, 14
Specialty Banding	15, 16
Plastic Cable Ties	17 - 20
Non Metallic Banding	21 - 24
Steel Strapping & Seals.....	25
Steel Strapping Tools	26 - 27
Product Summary	28



www.bandngo.com

Scan QR code to go to website

Stainless Steel Banding – Type 201

Type 201 stainless steel, 2B finish, annealed

Length: 100 ft. (30 m) Packaging: self dispensing box

Also available in 100 lb (45 kg) coils



	BSB2012*	BSB2013	BNG2014	BNG2015	BNG2016
	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>
Width	1/4" - 6.5 mm	3/8" - 9.5 mm	1/2" - 13 mm	5/8" - 16 mm	3/4" - 19 mm
Thickness	.020 in - 0.5 mm	0.025 - .635 mm	.030" - .76 mm	.030" - .76 mm	.030" - .76 mm
Tensile Strength	700 lbs - 3112 N	1040 lbs - 4625 N	1710 lbs - 7606 N	1940 lbs - 8629 N	2290 lbs - 10186 N
Weight per coil	1.9 lbs .87 kg	3.2 lbs - 1.5 kg	5.5 lbs - 2.3 kg	6.4 lbs - 2.9 kg	7.7 lbs - 3.5 kg
Case Quantity "Q"	10 coils	5 coils	5 coils	5 coils	5 coils
Accessories	* SS304				
Buckle	TT2002, WC2002	TT2003, WC2003	TT2004	TT2005	TT2006
Tools	BT2440, LTC100	BT2440, LTC100	MTC2400, RTS240	MTC2400, RTS240	MTC2400, RTS240

Stainless Steel Banding – Type 316

Type 316 stainless steel, 2B finish, annealed

Length: 100 ft. (30 m) Packaging: self dispensing box



	BSB3163	BNG3164	BNG3165	BNG3166
	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>
Width	3/8" - 9.5 mm	1/2" - 13 mm	5/8" - 16 mm	3/4" - 19 mm
Thickness	0.025 - .635 mm	.030" - .76 mm	.030" - .76 mm	.030" - .76 mm
Tensile Strength	1040 lbs - 4625 N	1450 lbs - 6449 N	1850 lbs - 8230 N	2100 lbs - 9341 N
Weight per coil	3.2 lbs - 1.5 kg	5.5 lbs - 2.3 kg	6.5 lbs - 2.9 kg	7.7 lbs - 3.5 kg
Case Quantity "Q"	5 coils	5 coils	5 coils	5 coils
Accessories				
Buckle	TT3163, WC3163	TT3164	TT3165	TT3166
Tools	BT2440, MTC2400	MTC2400, RTS240	MTC2400, RTS240	MTC2400, RTS240

Heavy Duty Stainless Steel Banding – Type 201

Type 201 stainless steel

Overall Thickness: .044" (1.2 mm) Length: 100 ft. (30 m)

Packaging: self dispensing box

	BSBHD2016	BSBHD2018	BSBHD20110
	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>
Width	3/4" - 19 mm	1" - 25 mm	1 1/4" - 32 mm
Tensile Strength	3300 lbs - 14679 N	4500 lbs - 20017 N	5400 lbs - 24020 N
Weight per coil	11.6 lbs - 5.27 kg	13.7 lbs - 6.23 kg	17.2 lbs - 7.8 kg
Accessories			
Buckle	TTHD2016	TTHD2018	TTHD20110
Tools	HTC6000	HTC6000	HTC6000



Use heavy duty banding where extra strength is required, e.g. fastening heavy duty pole line hardware

Light Duty Stainless Steel Banding – Type 304

Type 304 stainless steel

Overall Thickness: .015" (.5 mm) to .020" (.6 mm) Length: 200 ft. (60 m) Packaging: self dispensing box

Also available in 1000 ft (300 m) coils and 100 lb (45 kg) coils

	BNGLD153044	BSBLD153045	BSBLD203044	BSBLD203046
	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>
Width	1/2" - 13 mm	5/8" - 16 mm	1/2" - 13 mm	3/4" - 19 mm
Thickness	.015"	.015"	.020"	.020"
Tensile Strength	600 lbs - 2668 N	1000 lbs - 4448 N	850 lbs - 3780 N	1250 lbs - 5560 N
Weight per coil	5.5 lbs - 2.3 kg	6.4 lbs - 2.9 kg	7.0 lbs - 3.2 kg	11.2 lbs - 5.1 kg
Case Quantity	5 coils	5 coils	5 coils	5 coils
Accessories				
Buckle	TT2004	TT2005	TT2004	TT2006
Wing Seal	WC2014	WC2015	WC2014	WC2016
Tools	BT2440 MTC2400 RTS240 RTS2230	BT2440 MTC2400 RTS240 RTS2230	BT2440 MTC2400 RTS240 RTS2230	BT2440 MTC2400 RTS240 RTS2230



Use Light Duty stainless steel banding for general fastening, e.g. fastening light duty signs; securing insulation cladding

PVC and PPP Coated Stainless Steel Banding – Type 316

Type 316 stainless steel with polyvinyl chloride (PVC) coating

Type 316 stainless steel with halogen-free polypropylene (PPP) coating

Overall Thickness: .043" (1.1 mm) Length: 66 ft. (20 m) Packaging: self dispensing box



	PVC3163-PPP3163	PVC3164-PPP3164	PVC3165-PPP3165	PVC3166-PPP3166
	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>
Width	3/8" - 9.5 mm	1/2" - 13 mm	5/8" - 16 mm	3/4" - 19 mm
Break Strength	450 lbs - 2001 N	590 lbs - 2624 N	750 lbs - 3336 N	900 lbs - 4003 N
Steel Thickness	.014" - .35 mm	.014" - .35 mm	.014" - .35 mm	.014" - .35 mm
Band Thickness	.043" - 1.1 mm	.043" - 1.1 mm	.043" - 1.1 mm	.043" - 1.1 mm
Weight per coil	2.2 lbs - 1 kg	3 lbs - 1.4 kg	3.5 lbs - 1.6 kg	4.1 lbs - 1.9 kg
Temp Range C (PVC)	-40 to 85	-40 to 85	-40 to 85	-40 to 85
Temp Range C (PPP)	-20 to 90	-20 to 90	-20 to 90	-20 to 90
Wing Seal	WC3163	WC3164	WC3165	WC3166
Tools	BT2440 RTS240 RTS2230	BT2440 RTS240 RTS2230	BT2440 RTS240 RTS2230	BT2440 RTS240 RTS2230

Use PVC or PPP coated banding in applications where extra corrosion protection, cushioning, or black colour is required.

Note: PPP is halogen free.

PPA Coated Stainless Steel Banding – Type 316

Type 316 stainless steel with halogen-free polyphthalamide (PPA) coating

Overall Thickness: .047" (1.2 mm) Length: 82.5 ft. (30 m) Packaging: self dispensing box



	PPA3163	PPA3164	PPA3165	PPA3166
	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>	<i>Imperial-Metric</i>
Width	3/8" - 9.5 mm	1/2" - 13 mm	5/8" - 16 mm	3/4" - 19 mm
Break Strength	505 lbs - 2246 N	670 lbs - 2980 N	840 lbs - 3736 N	1000 lbs - 4448 N
Steel Thickness	.016" - .4 mm	.016" - .4 mm	.016" - .4 mm	.016" - .4 mm
Band Thickness	.047" - 1.2 mm	.047" - 1.2 mm	.047" - 1.2 mm	.047" - 1.2 mm
Weight per coil	2.2 lbs 1 kg	3 lbs - 1.4 kg	3.5 lbs - 1.6 kg	4.1 lbs - 1.9 kg
Temp Range C	-40 to 150	-40 to 150	-40 to 150	-40 to 150
Wing Seal	WC3163	WC3164	WC3165	WC3166
Tools	BT2440 RTS240 RTS2230	BT2440 RTS240 RTS2230	BT2440 RTS240 RTS2230	BT2440 RTS240 RTS2230

Use PPA coated banding in applications where extra corrosion protection, exposure to high temperatures, cushioning, or black colour is required, and where halogen-free materials are specified

Stainless Steel Tiger Teeth Buckles – Type 201, Type 316

Type 201 stainless steel and Type 316 stainless steel

Packaging: 100 per box

Product	Stainless Steel	Banding Size Inches - mm	Width inches - mm	Thickness inches - mm	Weight/Box lbs - kg
TT2002	201	¼ - 6.5	.3 - 7.7	.051 - 1.3	.6 - .3
TT2003	201	3/8 - 9.5	.4 - 10.2	.051 - 1.3	.8 - .4
TT2004	201	1/2 - 13	.6 - 15.3	.059 - 1.5	1.8 - .8
TT2005	201	5/8 - 16	.8 - 20.5	.059 - 1.5	2 - .9
TT2006	201	3/4 - 19	1 - 25.4	.07 - 1.8	3.4 - 1.5
TT3163	316	3/8 - 9.5	.4 - 10.2	.051 - 1.3	.8 - .4
TT3164	316	1/2 - 13	.6 - 15.3	.059 - 1.5	1.8 - .8
TT3165	316	5/8 - 16	.8 - 20.5	.059 - 1.5	2 - .9
TT3166	316	3/4 - 19	1 - 25.4	.07 - 1.8	3.4 - 1.5



Use Tiger Teeth buckles with medium duty (.030" thick) type 201 stainless steel banding, e.g. fastening signs, traffic signals, and control boxes . Use Type 316 stainless steel buckles with Type 316 stainless steel banding for general fastening in marine or other saline corrosive environments, e.g. securing cables, control boxes

Stainless Steel Type 201 Heavy Duty Tiger Teeth Buckles

Packaging: 25 pieces per box

Product	Banding Size Inches - mm	Width inches - mm	Thickness inches - mm	Weight/Box lbs - kg
TTHD2006	3/4 - 19	2 - 50	3/32 - 2	1.8 - .8
TTHD2008	1 - 25	2 3/8 - 60	3/32 - 2	2.5 - 1.1
TTHD20110	1 1/4 - 32	2 3/4 - 70	3/32 - 2	3.2 - 1.5



Type 201 heavy duty stainless steel buckles are suitable for use in heavy duty general banding applications.

Banding: BSBHD2016, BSBHD2018, BSBHD20110

Tensioning tools: HTC6000

Stainless Steel Flared Leg (FLB) and Straight Leg (SLB) Brackets

Type 304 stainless steel Packaging: 50 per box Box Weight: 9 lbs (4 kg)

Extra strong, stainless steel brackets are suitable for fastening signs, control boxes and other fixtures to poles, columns, pillars or beams. Includes 5/16" stainless steel head hex bolt, stainless steel washer and plastic washer. Use with stainless steel banding (1/4" – 3/4").



Stainless Steel Wing Seals

Type 304 and Type 316 stainless steel Packaging: 100 per box

Product	Stainless Steel	Banding Size	Width Inches - mm	Thickness Inches - mm	Weight/Box Lbs - kg
WC2012	201	¼	.3 – 7.7	.027 - .7	.6 - .3
WC2013	201	3/8	.5 – 12.8	.027 - .7	.8 - .4
WC2014	201	1/2	.9 – 23	.031 - .8	1.1 - .5
WC2015	201	5/8	1 – 25.4	.031 - .8	1.3 - .6
WC2016	201	3/4	1.1 – 28.6	.039 – 1.0	2.2 – 1.0
WC3163	316	3/8	.6 – 15.3	.027 - .7	.8 - .4
WC3164	316	1/2	1 – 25.4	.031 - .8	1.1 - .5
WC3165	316	5/8	1.1 – 28.1	.031 - .8	1.3 - .6
WC3166	316	3/4	1.3 – 33.3	.039 – 1.0	2.2 – 1.0



Use Type 304 stainless steel Wing Seals with light duty (.015" - .020" thick) stainless steel banding for general fastening applications, e.g. fastening light signs, securing insulation.
Use Type 316 stainless steel wing seals with Type 316 stainless steel banding or coated banding for general fastening in marine or other saline corrosive environments, e.g. securing cables, control boxes, sensors or in applications where black banding is preferred.

Stainless Steel Seals

Type 304 stainless steel
100 pieces per box
Use with light duty
stainless steel banding

Product	Style	Band Size	Width i.d. inches - mm	Weight/Ctn lbs - kg
4120100-C	open	1/2	.57 - 14	.77 - .35
4120100	push	1/2	.57 - 14	1.1 - .48
4340100-C	open	3/4	.81 - 20	.84 - .38
4340100	push	3/4	.81 - 20	1.5 - .66



Open



Push

Stainless Steel Screw Buckles

Packaging: 25 pieces per bag

Product	Banding	Width	Length	Set Screw Size	Weight/Ctn
SCR2014	1/2	11/16 - 18	9/16 - 14	Cup pt hex hd ¼ - 20	.5 - .225
SCR2016	¾	1 - 25	5/8 - 16	Cup pt hex hd ¼ - 20	.95 - .425



Stainless steel screw buckles are suitable for temporary or permanent fastening or for use in tight spaces.
Use with stainless steel strapping. Allen key included in bag.

WDS220 – Stainless Steel Worm Drive Seal

Packaging: 10 pieces per bag

Use WDS220 with 3/8" [9.5 mm] stainless steel banding for light weight fastening.
Comprised of stainless steel perforated band and stainless steel clasp.
Tension with Hex head or Flat screw driver.



Bolt Clamp for Heavy Duty Stainless Steel Banding

Packaging: Each

BCST500 - 3/4"W with 3/8"x6" bolt

BCST504 - 1 1/4"W with 5/8"x8" bolt

Twin aluminum housings with connecting heavy duty galvanized steel carriage bolt, nut and washer.
Fit ends of banding loop through slots in housings and tighten clamp by turning nut with wrench.



Pre-Cut Stainless Steel Strap with Tiger Teeth Buckle – Type 201**

Type 201 stainless steel Packaging: bundle

Product Number	Length Inches - mm	Width Inches - mm	Thickness Inches - mm
PCS360M13	14 - 360	1/2 - 13	.030 - .75
PCS360M19	14 - 360	3/4 - 19	.030 - .75
PCS680M13	26 - 680	1/2 - 13	.030 - .75
PCS680M19	26 - 680	3/4 - 19	.030 - .75
PCS1000M13	39 - 1000	1/2 - 13	.030 - .75
PCS1000M19	39 - 1000	3/4 - 19	.030 - .75

Tools: MTC2400, RTS240



Pre-Cut Stainless Steel Strap with Wing Seal – Type 304**

Type 304 stainless steel Packaging: bundle

Product Number	Length Inches - mm	Width Inches - mm	Thickness Inches - mm
PCS360L13	14 - 360	1/2 - 13	.015 - .38
PCS360L19	14 - 360	3/4 - 19	.020 - .51
PCS680L13	26 - 680	1/2 - 13	.015 - .38
PCS680L19	26 - 680	3/4 - 19	.020 - .51
PCS1000L13	39 - 1000	1/2 - 13	.015 - .38
PCS1000L19	39 - 1000	3/4 - 19	.020 - .51

Tools: MTC2400, RTS240,
RTS2230, BT2440



Pre-Cut Coated Stainless Steel Strap with Wing Seal – Type 316**

PPA Coated Type 316 stainless steel Packaging: bundle

Product Number	Length Inches - mm	Width Inches - mm	Thickness Inches - mm
PCS360A13	14 - 360	1/2 - 13	.047 - 1.2
PCS360A16	14 - 360	5/8 - 16	.047 - 1.2
PCS680A13	26 - 680	1/2 - 13	.047 - 1.2
PCS680A16	26 - 680	5/8 - 16	.047 - 1.2
PCS1000A13	39 - 1000	1/2 - 13	.047 - 1.2
PCS1000A16	39 - 1000	5/8 - 16	.047 - 1.2

Tools: RTS240, RTS2230,
BT2440



PCSBC – Pre-cut Strap with Bolt Clamp**

The PCSBC consists of a heavy duty bolt clamp and a custom length of ¾" or 1 ¼" wide stainless steel banding. Examples:

PCSBC380648 - 3/8" bolt x 3/4" x 48" band, max dia. 13"

PCSBC581060 - 5/8" bolt x 1 1/4" x 60" band, max dia 17"

Use to secure pole line hardware

****Contact Sales for sizes not displayed on this page.**



MTC2400 –Banding Tool with Cutter

Medium duty tool tensions and cuts stainless steel banding widths from ¼" to ¾" and thicknesses from .015" (.4 mm) to .030" (.7 mm)

Turn handle to tension, push lever to cut.

Use with **BNG, BSB** and **BNGLD, BSBLD** series banding

Shipping Weight: 4.2 lbs (1.9kg)

Box Dimensions: 9.5" (240 mm) x 4.5" (115 mm) x 3" (80 mm)

(Scan QR code for demonstration video)



HTC6000 – Heavy Duty Banding Tool with Cutter

Heavy duty tool tensions and cuts stainless steel banding widths from 1/2" (13 mm) to 1 1/4" (32 mm) and thicknesses from .020" (.5 mm) to .044" (1.1 mm)

All steel construction. Use for heavy duty banding or when extra tension is required.

Turn handle to tension, push lever to cut.

Use with **BSBHD** series stainless steel banding.

Shipping Weight: 11 lbs (5 kg)

Box Dimensions: 15" (380 mm) x 6" (150 mm), x 6" (150 mm)



RTS240–Ratchet Banding Tool with Cutter

Medium duty tool tensions and cuts stainless steel banding widths from ¼" (6 mm) to ¾" (19 mm) and thicknesses from .015" (.4 mm) to .030" (.7 mm)

Lever handle to tension, push handle to cut

Use with **BNG, BSB, BNGLD, BSBLD** and **coated banding**

Shipping Weight: 3.5 lbs (1.6kg)

Box Dimensions: 12" (300 mm) x 3" (75 mm) x 2" (50 mm)

(Scan QR code for demonstration video)



RTS2230–Ratchet Banding Tool with Cutter

Medium duty tool tensions and cuts steel or stainless steel banding widths from ¼" (6 mm) to ¾" (19 mm) and thicknesses from .015" (.4 mm) to .023" (.6 mm)

Lever handle to tension, squeeze handle to cut

Use with **BNGLD, BSBLD, PPA316, PVC316** and **PPP316** series stainless steel banding, and with **steel strapping**

(Scan QR code for demonstration video)



BT2440 – Squeeze Action Band Tensioning Tool with Cutter

Squeeze action tool tensions and cuts stainless steel banding or steel strapping widths from ¼" (6 mm) to ¾" (19 mm) and thicknesses from .015" (.4 mm) to .025" (.6 mm). Slots in nose and mandrel are .07" (2 mm) to accommodate coated banding.

Squeeze handles to tension, push lever to cut.

Use with **BNGLD**, **BSBLD** stainless steel banding and **PPA316**, **PVC316** or **PPP316** series coated stainless steel banding.

Shipping Weight: 2.8 lbs (1.3kg)

Box Dimensions: 7" (180 mm) x 7.5" (190 mm) x 3" (75 mm)

(Scan QR code for demonstration video)



LTC100 –Banding Tool with Cutter

Light duty tool tensions and cuts stainless steel banding with widths from ¼" (6 mm) to 3/8" (9.5 mm) and thicknesses from .010" (.2 mm) to .025" (.6 mm)

Use with **BSB2013** stainless steel banding or with 3/8" wide "J" series preformed clamps

Shipping Weight: 1.0 lbs (.4kg)

Box Dimensions: 8.0" (200 mm) x 2.0" (50 mm) x 1.5" (40 mm)

(Scan QR code for demonstration video)



PB2100 – Push-Bar Tensioning Tool

Light to Medium duty tool tensions stainless steel banding or steel strapping with widths from ¼" (6 mm) to 3/4" (19 mm) and thicknesses from .015" (.4 mm) to .020" (.5 mm)

Use with **BNGLD**, **BSBLD** series stainless steel banding or steel strapping and steel or stainless steel seals.

Shipping Weight: 3 lbs (1.4kg)

Box Dimensions: 10" (26 mm) x 6" (150 mm) x 3" (75 mm)



PT2680 – Punch Tool

Medium duty tool tensions and seals stainless steel (HBCPS) or galvanized (HBCPG) 5/8" (16 mm) wide centre punch pre-formed clamps

Shipping Weight: 3 lbs (1.4kg)

Box Dimensions: 14" (360 mm) x 4" (100 mm) x 4" (100 mm)

Available adaptor for 3/8" wide clamps



150 lb. Stainless Steel Ball-Lock Cable Ties

Product Number Mill	Product Number Coated	Product Number Type 304 SS*	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lb
KSS100	KSS100C	KSS100-4	100 - 4	25 - 1	.17 - .37
KSS150	KSS150C	KSS150-4	150 - 6	39 - 1.5	.21 - .46
KSS200	KSS200C	KSS200-4	200 - 8	50 - 2	.26 - .57
KSS360	KSS360C	KSS360-4	360 - 14	100 - 4	.42 - .92
KSS520	KSS520C	KSS520-4	520 - 20	150 - 6	.56 - 1.23
KSS680	KSS680C	KSS680-4	680 - 26	200 - 8	.70 - 1.54
KSS840	KSS840C	KSS840-4	840 - 33	250 - 10	.87 - 1.91
KSS1000	KSS1000C	KSS1000-4	1000 - 39	300 - 12	1.04 - 2.29
KSS1200	KSS1200C	KSS1200-4	1200 - 47	365 - 14	1.24 - 2.73
KSS1400	KSS1400C	KSS1400-4	1400 - 55	425 - 17	1.44 - 3.17



Type 316 stainless steel
Width 4.6mm (.18")
 Thickness: .010"
 Coated – Thickness: .013"
 Package: 100 per bag



*Type 304 stainless steel cable ties are not listed with approvals agencies.

300 lb. Stainless Steel Ball-Lock Cable Ties

Product Number Mill	Product Number Coated	Product Number Type 304 SS*	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lb
KSS200H	KSS200HC	KSS200H-4	200 - 8	50 - 2	.51 - 1.1
KSS360H	KSS360HC	KSS360H-4	360 - 14	100 - 4	.77 - 1.6
KSS520H	KSS520HC	KSS520H-4	520 - 20	150 - 6	1.0 - 2.2
KSS680H	KSS680HC	KSS680H-4	680 - 26	200 - 8	1.28 - 2.8
KSS840H	KSS840HC	KSS840H-4	840 - 33	250 - 10	1.54 - 3.3
KSS1000H	KSS1000HC	KSS1000H-4	1000 - 39	300 - 12	1.77 - 3.8
KSS1200H	KSS1200HC	KSS1200H-4	1200 - 47	365 - 14	2.04 - 4.4
KSS1400H	KSS1400HC	KSS1400H-4	1400 - 55	425 - 17	2.34 - 5.1

Type 316 stainless steel
Width 7.8mm (.31")
 Thickness: .010"
 Coated – Thickness: .013"
 Package: 100 per bag



*Type 304 stainless steel cable ties are not listed with approvals agencies.

450 lb. Stainless Steel Ball-Lock Cable Ties

Product Number Mill	Product Number Coated	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lbs
KSS200XHD	KSS200XHDC	200 - 8	50 - 2	.51 - 1.5
KSS290XHD	KSS290XHD	290 - 11	80 - 3	1.0 - 2.2
KSS360XHD	KSS360XHDC	360 - 14	100 - 4	1.3 - 2.9
KSS520XHD	KSS520XHDC	520 - 20	150 - 6	1.8 - 4.0
KSS680XHD	KSS680XHDC	680 - 26	200 - 8	2.4 - 5.3
KSS840XHD	KSS840XHDC	840 - 33	250 - 10	2.9 - 6.4
KSS1000XHD	KSS1000XHDC	1000 - 39	300 - 12	3.4 - 7.5



Type 316 stainless steel
Width 12.5mm (.50")
 Thickness: .010"
 Coated – Thickness: .013"
 Package: 100 per bag



800 lb. Stainless Steel Ball-Lock Cable Ties

Type 316 stainless steel **Width 15.88mm (0.625")** Thickness: 0.35mm (.014") [coated .47mm(.018")], 50 per bag

Product Number Mill	Product Number Coated	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lbs
KSS457XXHD	KSS457XXHDC	457 - 18	109 - 4.3	.41 - .91
KSS610XXHD	KSS610XXHDC	610 - 24	158 - 6.2	.54 - 1.2
KSS762XXHD	KSS762XXHDC	762 - 30	206 - 8.1	.63 - 1.4



Aluminum Ball-Lock Cable Ties

50 lb. break strength, 7.9mm (0.31") width x 0.30mm (.010") thick, 100 per bag

Product Number Mill	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lbs
KSS150AL	150 - 6	39 - 1.5	.11 - .24
KSS200AL	200 - 8	51 - 2	.12 - .27



100 lb. Stainless Steel Ladder Style Cable Ties

Product Number Mill	Product Number Coated	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lbs
KSSLT200/7	KSSLT200/7C	200 - 8	50 - 2	.26 - .57
KSSLT225/7	KSSLT225/7C	225 - 9	60 - 2.5	.27 - .59
KSSLT300/7	KSSLT300/7C	300 - 12	70 - 3	.28 - .62
KSSLT360/7	KSSLT360/7C	360 - 12	100 - 4	.42 - .92
KSSLT450/7	KSSLT450/7C	450 - 18	150 - 6	.56 - 1.23
KSSLT610/7	KSSLT610/7C	610 - 24	200 - 8	.70 - 1.54
KSSLT750/7	KSSLT750/7C	750 - 30	250 - 10	.87 - 1.91
KSSLT1000/7	KSSLT1000/7C	1000 - 39	300 - 12	1.04 - 2.29

Type 316 stainless steel - 7mm (0.28") width x 0.26mm (.010") thick [coated .33mm (.013") thick], 100 per bag



250 lb. Stainless Steel Ladder Style Cable Ties

Product Number Mill	Product Number Coated	Length mm - inches	Max bundle mm - inches	Bag Weight kg - lbs
KSSLT200/12	KSSLT200/12C	200 - 8	50 - 2	.26 - .57
KSSLT225/12	KSSLT225/12C	225 - 9	60 - 2.5	.27 - .59
KSSLT300/12	KSSLT300/12C	300 - 12	70 - 3	.28 - .62
KSSLT360/12	KSSLT360/12C	360 - 14	100 - 4	.42 - .92
KSSLT450/12	KSSLT450/12C	450 - 18	150 - 6	.56 - 1.23
KSSLT610/12	KSSLT610/12C	610 - 24	200 - 8	.70 - 1.54
KSSLT750/12	KSSLT750/12C	750 - 30	250 - 10	.87 - 1.91
KSSLT1000/12	KSSLT1000/12C	1000 - 39	300 - 12	1.04 - 2.29

Type 316 stainless steel - 12mm (0.47") width x 0.26mm (.010") thick [coated .33mm (.013") thick]. 100 per bag



CT2850 – Cable Tie Tensioning Tool with Cutter

Squeeze-action tool tensions & cuts stainless steel cable ties

Push lever down to cut

Cable ties: 4.6mm [.18"] to 12.5mm [1/2"] x .25mm [.01"] to .35mm [.02"]

Weight: 1.5 lbs

(Scan QR code for demonstration video)



CT2840 – Cable Tie Tensioning Tool with Auto-Tension Cutter

Pistol Grip tool tensions & cuts stainless steel cable ties

Cable ties: 4.6mm [.18"] to 7.9mm [.31"] x .25mm [.01"]

Pre-set automatic cut-off tension

When cable tie reaches desired tightness, tool automatically cuts off tail

Weight: 2 lbs

(Scan QR code for demonstration video)



SKG-T001 - Lever Handle Ratchet Tool with Cutter

Compact tool tensions and cuts stainless steel cable ties

Lever wrench to actuate ratchet tensioning. Squeeze handles to cut.

Cable ties: 4.6 mm (.18") to 16 mm (.625") W x .30 mm (.012") T

Weight: 518 g (1.14 lbs)



HTOOL - Hook Tool

"T" - handle manual pull tensioning tool for stainless steel cable ties with hole in tail.

110mm [4.5"] W x 90mm [3.5"] L

Weight: 2 oz



Strapbinder® – Smooth-Seal™**Centre Punch Pre-Formed Hose Clamps****5/8" [16 mm] wide x .027" [.7 mm] thick****Available in Galvanized Carbon Steel or Type 201 Stainless Steel**

Product Number Stainless	Product Number Galvanized	Clamp ID Inches - mm	Box Qty	Box Weight lb - kg
HBCP4S	HBCP4	1 - 25.4	100	8.3 - 3.8
HBCP5S	HBCP5	1 ¼ - 31.7	100	8.7 - 3.9
HBCP6S	HBCP6	1 ½ - 38.1	100	9.7 - 4.4
HBCP7S	HBCP7	1 ¾ - 44.5	100	10.6 - 4.8
HBCP8S	HBCP8	2 - 50.8	100	11.5 - 5.2
HBCP9S	HBCP9	2 ¼ - 57.1	100	12.6 - 5.7
HBCP10S	HBCP10	2 ½ - 63.5	50	6.8 - 3.1
HBCP11S	HBCP11	2 ¾ - 69.85	50	7.3 - 3.3
HBCP12S	HBCP12	3 - 76.2	50	7.7 - 3.5
HBCP14S	HBCP14	3 ½ - 88.9	50	8.7 - 3.9
HBCP16S	HBCP16	4 - 101.6	25	4.9 - 2.2
HBCP18S	HBCP18	4 ½ - 114.3	25	5.5 - 2.5
HBCP20S	HBCP20	5 - 127	25	5.9 - 2.7
HBCP24S	HBCP24	6 - 152.4	25	6.8 - 3.1
HBCP28S	HBCP28	7 - 177.8	25	7.4 - 3.4
HBCP32S	HBCP32	8 - 203.2	25	8.2 - 3.7

3/8" (9.5 mm) x .027" (.70 mm) thick**Available in Galvanized Carbon Steel or Type 201 Stainless Steel**

Product Number Stainless	Product Number Galvanized	Clamp ID inches - mm	Box Qty	Box Weight lbs - kg
HBCP3S	HBCP3	13/16 - 20.6	100	3.6 - 1.6
HBCP311S	HBCP311	1 3/8 - 34.9	100	4.6 - 2.1

To select the proper size, measure the outside diameter of the hose *with the fitting inserted*. Choose the next larger inside diameter clamp.

To fasten, use **PT2680** tool (page 9).

To select the proper size, measure the outside diameter of the hose *with the fitting inserted*. Choose the next larger inside diameter clamp.

To fasten, use **PT2680** Centre Punch tool with **PTAdapt** Adapter for 3/8" wide bands.



Strapbinder® – Smooth-Seal™

“J” Series Pre-Formed Hose Clamps

Available in Type 201 Stainless Steel and Galvanized Carbon Steel



Product Number Stainless	Product Number Galvanized	Clamp ID inches - mm	Band Width inches - mm	Band Thickness Inches - mm	Box Qty	Box Weight lb - kg
HBJS201	HBJS301	13/16 - 20.6	3/8 - 9.5	0.025 - 0.65	100	3.6 - 1.6
HBJS242		1 - 25.4	1/4 - 6	0.02 - 0.51	100	2.1 - 0.9
HBJS243	HBJS343	1 - 25.4	3/8 - 9.5	0.025 - 0.65	100	3.4 - 1.5
HBJS202	HBJS302	1 3/8 - 34.9	3/8 - 9.5	0.025 - 0.65	100	4.7 - 2.1
HBJS203		1 - 25.4	1/2 - 13	0.03 - 0.76	100	6.5 - 2.9
HBJS204	HBJS304	1 1/4 - 31.7	1/2 - 13	0.03 - 0.76	100	7.2 - 3.3
HBJS241		1 3/8 - 34.9	1/4 - 6	0.02 - 0.51	100	2.5 - 1.1
HBJS205	HBJS305	1 1/2 - 38.1	5/8 - 16	0.03 - 0.76	100	10.4 - 4.7
HBJS206	HBJS306	1 3/4 - 44.4	5/8 - 16	0.03 - 0.76	100	11.3 - 5.1
HBJS245		2 - 50.8	3/8 - 9.5	0.025 - 0.65	100	5.5 - 2.5
HBJS207	HBJS307	2 - 50.8	5/8 - 16	0.03 - 0.76	100	12.2 - 5.5
HBJS208		2 1/4 - 57.1	5/8 - 16	0.03 - 0.76	100	13.3 - 6.1
HBJS209	HBJS309	2 1/2 - 63.5	5/8 - 16	0.03 - 0.76	100	13.9 - 6.3
HBJS210		2 3/4 - 69.8	3/4 - 19	0.03 - 0.76	100	9.2 - 4.2
HBJS211		3 - 76.2	3/4 - 19	0.03 - 0.76	50	9.7 - 4.4
HBJS212	HBJS312	3 1/2 - 88.9	3/4 - 19	0.03 - 0.76	50	10.8 - 4.9
HBJS213	HBJS313	4 - 101.6	3/4 - 19	0.03 - 0.76	25	6.1 - 2.8
HBJS214	HBJS314	4 1/2 - 114.3	3/4 - 19	0.03 - 0.76	25	6.7 - 3.1
HBJS215	HBJS315	5 - 127	3/4 - 19	0.03 - 0.76	25	7.2 - 3.3
HBJS216		6 - 152.4	3/4 - 19	0.03 - 0.76	25	8.2 - 3.7
HBJS218		7 - 177.8	3/4 - 19	0.03 - 0.76	25	10.2 - 4.6
HBJS219		8 - 203.2	3/4 - 19	0.03 - 0.76	25	11 - 5.1

To select the proper size, measure the outside diameter of the hose *with the fitting inserted*. Choose the next larger inside diameter clamp.

To fasten any size, use **MTC2400** tool (page 8) with “J” Series clamp tool adapter.

For electrical use, secure cable pulls with 1/4” and 3/8” wide clamps with **LTC100** tool (page 9).


HS 54123 - Stainless Steel Hanger Strap - 1/2"

1/2" [13 mm] x .028" [.7 mm] x 32 ft [10 m] punched stainless steel banding, with 7/32" (5.8 mm) holes at 13/32" (10 mm) centres, on plastic spool - 6" (150 mm) o.d. x 1" (25 mm). Wt. 3 lbs [1.36 kg]. Use it for general bundling, fastening and hanging applications.



HS 54116 – Galvanized Steel Hanger Strap – 5/8"

5/8" (17mm) x .028" (.7mm) with 17/64" (6.5 mm) diameter holes at 13/16" (19.8 mm) centres. 33 ft (10m) on self-dispensing plastic spool – 6" (150 mm) dia. X 1 Use it for general bundling, fastening and hanging applications.



RBC1000/10 – Ratchet Band Clamp

Ratchet Band Clamp consists of a stainless steel band affixed to a specially designed clasp with integral ratchet tension wheel and lever.

No tensioning tools are required to tension the RBC1000/10.

1000mm (39") x 0.2mm (0.0079" [35 GA]) x 10mm (0.4") hemmed band with 1mm thick ratchet clamp. Type 304 stainless steel. Sold 20 pieces per polybag. Bag Weight: 0.73kg (1.6lbs)



(Scan QR code for demonstration video)


BNC03220 Band-N-Clamp Kit

The Band-N-Clamp Kit consists of one 100 ft coil 3/8" (9.5 mm) stainless steel banding and twenty sets of WDS220 worm drive seal (rack & screw housing).

Tension banding by turning a screw

100 ft (30 m) 3/8" stainless steel banding.

Worm Drive Seal - includes rack with hole to insert banding, and screw housing with hole to insert banding



SKG-HPB - TURNTITE™ Stainless Steel Band Clamp

Band Clamp tensions with the turn of a screw.

Can be double wrapped for extra strength. No special tensioning tools required

10 mm W x .3 mm T, operating temp -80C to 400C, 1000 lb strength, 5 per bag

Product Number Sizes (mm): **SKG-HPB500, SKG-HPB1000, SKG-HPB1500, SKG-HPB2000, SKG-HPB2500, SKG-HPB3000**



(Scan QR code for demonstration video)



SKG-SCT - Pin Type Stainless Steel Cable Ties

Unique stainless steel cable ties that are releasable and reusable

Type A: 5 mm wide x .3 mm (.012") thick, 100 lb (450N) strength

Product Number-Lengths (mm): **SKG-SCTA-200, SKG-SCTA-360, SKG-SCTA-520, SKG-SCTA-680**

Type B: 14 mm wide x .3 mm (.012") thick, 390 lb (1750N) strength

Product Number-Lengths (mm): **SKG-SCTB-360, SKG-SCTB-520, SKG-SCTB-680, SKG-SCTB-840, SKG-SCTB-1000**

Fastening Tool: **SKG-T001**



SKG-T001 (page 12)



Type A



Type B

Plastic Cable Ties

18 lb. Miniature Plastic Cable Ties

Nylon 66 – 2.4mm (0.09”) width x 1.06mm (.04”) thick, 100 per bag

Tensile Strength: 18 lbs/80N

Operating Temp: -40 to 185 F; Min Install Temp: -4F, -20C

Min Bundle Diameter: .06 in, .015 mm

Approvals & Listings: UL, CSA Type 21; Plenum Rating: UL, CSA AH-2; Flame Rating: UL 94V-2

RoHS Compliant

Product of USA



Part Number	Colour	Length Inches - mm	Max Bdl dia. inches - mm	Mil Spec Reference	Bag Qty*	Bag Weight lb - kg
AL-04-18-0-C	UV Black	4.1 - 104.7	0.8 - 22.2	MS3367-4-0	100	.09 - .04
AL-06-18-0-C	UV Black	6.1 - 157.1	1.5 - 38.1		100	.12 - .05
AL-08-18-0-C	UV Black	8.1 - 207.9	2.1 - 55.5		100	.16 - .07

*Also Available in bags of 1000. Available in Natural (-9)

Also available in colours by special order: 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Purple, 8-Gray, 11-Fluorescent Green, 12-Fluorescent Pink, 13-Fluorescent Yellow, 14-Fluorescent Orange, 15-Fluorescent Blue, 18-Pink - contact sales for ordering information. MOQ's may apply

40 lb. Intermediate Plastic Cable Ties

Nylon 66 – 3.5 mm (0.14”) width x 1.24mm (.04”) thick, 100 per bag

Tensile Strength: 40 lbs/178N

Operating Temp: -40 to 185 F; Min Install Temp: -4F, -20C

Min Bundle Diameter: .06 in, .015 mm

Approvals & Listings: UL, CSA Type 21 Plenum Rating: UL, CSA AH-2; Flame Rating: UL 94V-2; RoHS Compliant

Product of USA



Part Number	Colour	Length inches - mm	Thickness inches - mm	Max Bdl. dia. inches - mm	Mil Spec Ref	Bag Qty*	Bag Weight lbs - kg
AL-05-40-0-C	UV Black	5.84 - 148.3	0.04 - 1.24	1.43 - 36.42	MS3367-5-0	100	.19 - .08
AL-08-40-0-C	UV Black	8.87 - 225.4	0.04 - 1.24	2.37 - 60.32		100	.27 - .12
AL-11-40-0-C	UV Black	10.96 - 278.5	.05 - 1.37	3.37 - 85.72		100	.34 - .15
AL-14-40-0-C	UV Black	14.25 - 361.9	.05 - 1.37	4.0 - 101.6		100	.44 - .20

5" & 8" also available in bags of 1000. 11" & 14" also available in bags of 500. All sizes available in Natural (-9)

Also available in natural nylon and colours by special order: 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Purple, 8-Gray, 11-Fluorescent Green, 12-Fluorescent Pink, 13-Fluorescent Yellow, 14-Fluorescent Orange, 15-Fluorescent Blue, 18-Pink

- contact sales for ordering information. MOQ's may apply

Plastic Cable Ties

50 lb. Standard Plastic Cable Ties*

Nylon 66 – 4.5 mm (0.18") width x 1.32mm (.05") thick

Tensile Strength: 50 lbs/220N



Part Number	Colour	Length in - mm	Max Bdl.dia. in - mm	Mil Spec Ref	Bag Qty	Bag Weight lbs - kg
AL-07-50-0-C	UV Bk	7.5 - 192.1	1.8 - 47.6	MS3367-1-0	100	.31 - .14
AL-07-50-0-M	UV Bk	7.5 - 192.1	1.8 - 47.6	MS3367-1-0	1000	3.0 - 1.4
AL-11-50-0-C	UV Bk	11.2 - 285.7	3.0 - 77.7	MS3367-7-0	100	.46 - .21
AL-11-50-0-D	UV Bk	11.2 - 285.7	3.0 - 77.7	MS3367-7-0	500	2.2 - 1
AL-14-50-0-C	UV Bk	14.3 - 364.4	4.0 - 101.6	MS3367-2-0	100	.56 - .25
AL-14-50-0-D	UV Bk	14.3 - 364.4	4.0 - 101.6	MS3367-2-0	500	2.7 - 1.22

Operating Temp: -40 to 185F
 Min Install temp: -4F (-20C)
 Min Bundle dia. .06 in (0.15mm)
 UL & CSA: Type 21S
 Plenum Rating: UL, CSA AH-2
 Flame Rating: UL94V-2
 RoHS Compliant
 Product of USA

*Also available in natural nylon and colours by special order: 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Purple, 8-Gray, 9-natural, 11-Fluorescent Green, 12-Fluorescent Pink, 13-Fluorescent Yellow, 14-Fluorescent Orange, 15-Fluorescent Blue, 18-Pink. Contact sales for ordering information. MOQ's may apply

120 lb. Light Heavy Duty Plastic Cable Ties*

Nylon 66 – 7.6 mm (0.30") width x 1.93mm (.07") thick

Tensile Strength: 120 lbs/534N



Part Number	Colour	Length in - mm	Max Bdl. dia. in - mm	Mil Spec Ref	Bag Qty	Bag Weight lbs - kg
AL-08-120-0-C	UV Bk	8.7 - 220.9	2 - 52		100	.9 - .4
AL-14-120-0-C	UV Bk	14.8 - 376.6	4 - 103	MS3367-3-0	100	1.45 - .66
AL-14-120-0-L	UV Bk	14.8 - 376.6	4 - 103	MS3367-3-0	50	.72 - .33
AL-18-120-0-L	UV Bk	18 - 457	5 - 125		50	0.88 - .40
AL-24-120-0-L	UV Bk	24 - 610	7 - 175		50	1.17 - .53
AL-30-120-0-L	UV Bk	30 - 762	9 - 225	MS3367-6-0	50	1.46 - .66
AL-36-120-0-L	UV Bk	36 - 914	11 - 275		50	1.75 - .80

Operating Temp: -40 to 185F
 Min Install temp: -4F (-20C)
 Min Bundle dia. .06 in (0.15mm)
 UL & CSA: Type 21S
 Plenum Rating: UL, CSA AH-2
 Flame Rating: UL94V-2
 RoHS Compliant
 Product of USA

*Also available in natural nylon and colours by special order: 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Purple, 8-Gray, 9-natural, 11-Fluorescent Green, 11UV-Fluorescent Green, 12-Fluorescent Pink, 14-Fluorescent Orange, 15-Fluorescent Blue, 18-Pink. Contact sales for ordering information. MOQ's may apply

Plastic Cable Ties

175 lb. Heavy Duty Plastic Cable Ties*

Part Number	Colour	Length in - mm	Max Bdl. dia. in - mm	Mil Spec Ref	Bag Qty	Bag Weight lbs - kg
AL-24-175-0-L	UV Black	25 - 641	7 - 182	MS3367-10-0	50	1.6 - .73
AL-36-175-0-L	UV Black	37 - 946	11 - 279	MS3367-13-0	50	2.3 - 1
AL-48-175-0-L	UV Black	48 - 1233	14 - 368	MS3367-16-0	50	2.9 - 1.3

*Also available in Natural and Gray



Nylon 66
 Width: 3/4" (8.6 mm)
 Thick: .09" (2.29 mm)
 Tensile Strength: 175 lbs / 778N
 Operating Temp: -40 to 185 F;
 Min Install Temp: -4F, -20C
 Approvals/Listings: UL, CSA Type 21;
 also rated UL 181B-C for HVAC
 Plenum Rating: UL, CSA AH-2
 Flame Rating: UL 94V-2
 RoHS Compliant
 Product of USA

Cold Weather Plastic Cable Ties

Part Number	Length in - mm	Width in - mm	Thickness in - mm	Max. Bdl. Dia. in - mm	Tensile Strength lb - N	Bag Weight lbs - kg
AL-07-50-CW-0-C	7.56 - 192.07	0.18 - 4.57	0.05 - 1.32	1.87 - 47.62	50 - 222	.31 - .14
AL-11-50-CW-0-C	11.25 - 285.7	0.18 - 4.57	0.05 - 1.32	3.06 - 77.77	50 - 222	.46 - .22
AL-14-50-CW-0-C	14.35 - 364.49	0.18 - 4.57	0.05 - 1.32	4.00 - 101.6	50 - 222	.56 - .25
AL-14-120-CW-0-C	14.82 - 376.63	0.30 - 7.62	0.07 - 1.93	4.06 - 103.12	120 - 534	1.45 - .66

Nylon 66 – 100 per bag
 Colour: UV Black
 Operating Temp: -40 to 149F
 Minimum Installation Temp: -4 F
 UL & CSA Type 11
 Flame Rating: UL 94 HB
 RoHS Compliant
 Product of USA

Nylon 12 Solar Plastic Cable Ties

Part Number	Length in - mm	Width in - mm	Thickness in - mm	Max. Bdl. Dia. in - mm	Tensile Strength lb - N	Bag Weight lbs - kg
AL-05-40-NY12-0-C	5.84 - 148.33	0.14 - 3.55	0.04 - 1.24	1.43 - 36.42	40 - 178	.19 - .08
AL-07-50-NY12-0-C	7.56 - 192.07	0.18 - 4.57	0.05 - 1.32	1.87 - 47.62	50 - 222	.31 - .14
AL-11-50-NY12-0-C	11.25 - 285.75	0.18 - 4.57	0.05 - 1.32	3.06 - 77.77	50 - 222	.46 - .22
AL-14-50-NY12-0-C	14.35 - 364.49	0.18 - 4.57	0.05 - 1.32	4.00 - 101.6	50 - 222	.56 - .25
AL-08-120-NY12-0-C	8.70 - 220.98	0.30 - 7.62	0.07 - 1.93	2.06 - 52.32	100 - 444	.90 - .41
AL-14-120NY12-0-C	14.82 - 376.63	0.30 - 7.62	0.07 - 1.93	4.06 - 103.12	100 - 444	1.45 - .66

Nylon 12 - 100 per bag
 Colour: UV Black
 Max Operating Temp.: 185 F / 85 C
 Flame rating: UL 94 HB
 RoHS Compliant
 Product of USA

Stainless Steel Pawl Plastic Cable Ties

Nylon 66

Colour: UV Black (-0); natural (-9)

Operating Temp.: -40 to 185F

RoHS Compliant

Product of Italy



Part Number	Length In - mm	Width In - mm	Thickness In - mm	Max. Bundle Dia. In - mm	Tensile Strength lb - N	Per Bag
ALB-04-18-SP	3.93 - 100.	.098 - 2.50	0.035 - 0.9	0.94 - 24.0	18 - 80	100
ALB-05-40-SP	5.51 - 140.	.137 - 3.50	0.039 - 1.0	1.42 - 36.0	40 - 178	100
ALB-07-50-SP	7.32 - 186.	.177 - 4.5	0.043 - 1.1	1.93 - 49.0	50 - 222	100
ALB-08-18-SP	7.87 - 200.	.098 - 2.50	0.035 - 0.9	2.17 - 55.0	18 - 80	100
ALB-08-40-SP	7.87 - 200.	.137 - 3.50	0.039 - 1.0	2.17 - 55.0	40 - 178	100
ALB-11-40-SP	11.0 - 280.	.137 - 3.50	0.039 - 1.0	3.15 - 80.0	40 - 178	100
ALB-11-50-SP	11.4 - 290.	.177 - 4.5	0.043 - 1.1	3.15 - 80.0	50 - 222	100
ALB-14-120-SP	14.1 - 360.	.295 - 7.5	0.059 - 1.5	3.98 - 101.0	120 - 534	50
ALB-14-50-SP	14.1 - 360.	.177 - 4.5	0.043 - 1.1	4.06 - 103.0	50 - 222	100

Tool for Plastic Cable Ties

PCT-5000

Tensions and cuts plastic cable ties up to 12.5 mm (.5") wide

Adjustable tension

All metal construction





Smart® Tie 20mm (3/4 inch)

Heavy duty polymer cable tie used in onshore and offshore hydrocarbon extraction operations and other demanding applications.

Product #	Length mm - in	Width mm - in	Thickness mm - in	Material*	Max Strength kgf - lbf	Max Temp C - F	Min Diameter** mm - in
ST-20PA66-450	450 - 18	20 - 3/4	3.6 - .14	PA66	513 - 1128	125 - 257	60 - 2.36
ST-20PA66-600	600 - 24	20 - 3/4	3.6 - .14	PA66	513 - 1128	125 - 257	60 - 2.36
ST-20PK-600	600 - 24	20 - 3/4	3.6 - .14	PK	565 - 1220	125 - 257	60 - 2.36
ST-20PA12-600	600 - 24	20 - 3/4	3.6 - .14	PA12	414 - 911	100 - 212	60 - 2.36
ST-20PPS-600	600 - 24	20 - 3/4	3.6 - .14	PPS	514 - 1130	175 - 347	60 - 2.36
ST-20PA66-750	750 - 30	20 - 3/4	3.6 - .14	PA66	513 - 1128	125 - 257	60 - 2.36
ST-20PK-750	750 - 30	20 - 3/4	3.6 - .14	PK	565 - 1220	125 - 257	60 - 2.36
ST-20PA12-750	750 - 30	20 - 3/4	3.6 - .14	PA12	414 - 911	100 - 212	60 - 2.36
ST-20PPS-750	750 - 30	20 - 3/4	3.6 - .14	PPS	514 - 1130	175 - 347	60 - 2.36

Smart® Tie 32mm (1 1/4 inch)

Extra Heavy Duty polymer cable tie used in onshore and offshore hydrocarbon extraction operations and other demanding applications.

Product #	Length mm - in	Width mm - in	Thickness mm - in	Material*	Max Strength kgf - lbf	Max Temp C - F	Min Diameter** mm - in
ST-32PK-550	550 - 21	32 - 1 1/4	4.6 - .18	PK	1270 - 2800	125 - 257	60 - 2.36
ST-32PA12-550	550 - 21	32 - 1 1/4	4.6 - .18	PA12	984 - 2169	105 - 221	60 - 2.36
ST-32PK-850	850 - 33	32 - 1 1/4	4.6 - .18	PK	1270 - 2800	125 - 257	60 - 2.36
ST-32PA12-850	850 - 33	32 - 1 1/4	4.6 - .18	PA12	984 - 2169	105 - 221	60 - 2.36
ST-32PPS-850	850 - 33	32 - 1 1/4	4.6 - .18	PPS	1223 - 2695	175 - 347	60 - 2.36

*PA66 – Polyamide 66 [Nylon 66]; PK – Polyketone [poly vinyl methyl ketone]; PA12 – Polyamide 12 [Nylon 12]

PPS – Polyphenylene Sulfide

**For very cold temperatures e.g. -40 C increase minimum diameter to 100 mm

For best results, Smart Tie should be installed when product temperature is close to room temperature.



HCL Smart® Band

Non-Metallic, Lightweight band and buckle system



HCL Smart® Band is a Glass Fibre Yarn reinforced Polymer Banding system and is available in a variety of materials. PA66 is suitable for temporary and permanent general banding e.g. fastening signs to poles, columns, pillars or beams. POM is very commonly used in the Marine industry and PA12 is an alternative to high grade corrosion resistant metals, e.g. Inconel, Monel and Titanium.

Tensioning tools: SM-FT-1000, SM-FT-2000, SM-FT-3000,

Buckles: SB-BU-1/4-ST, SB-BU-3/8-ST, SB-BU-3/4-S, SB-BU-3/4-HY, SB-BU-1-1/4-HY

Accessories: Smart Protector

Product #	Length m - ft	Width mm - in	Thickness mm - in	Material*	Max Strength kgf - lbf	Max Temp C - F	Min** Diameter mm - in
SB-BA-1/4-30M-PA66	30 - 100	7 - 1/4	2.6 - .1	PA66	90 - 197	125 - 257	100 - 3.94
SB-BA-1/4-250M-PA66	250 - 820	7 - 1/4	2.6 - .1	PA66	90 - 197	125 - 257	100 - 3.94
SB-BA-3/8-30M-PA12	30 - 100	10 - 3/8	3.6 - .14	PA12	127 - 280	100 - 212	76 - 2.96
SB-BA-3/8-125M-PA12	125 - 410	10 - 3/8	3.6 - .14	PA12	127 - 280	100 - 212	76 - 2.96
SB-BA-3/8-30M-PA66	30 - 100	10 - 3/8	3.6 - .14	PA66	264 - 581	125 - 257	76 - 2.96
SB-BA-3/8-125M-PA66	125 - 410	10 - 3/8	3.6 - .14	PA66	264 - 581	125 - 257	76 - 2.96
SB-BA-3/4-30M-POM	30 - 100	19 - 3/4	3.6 - .14	POM	1017 - 2238	95 - 203	100 - 4
SB-BA-3/4-60M-POM	60 - 200	19 - 3/4	3.6 - .14	POM	1017 - 2238	95 - 203	100 - 4
SB-BA-3/4-30M-PA66	30 - 100	19 - 3/4	3.6 - .14	PA66	440 - 969	125 - 260	100 - 4
SB-BA-3/4-60M-PA66	60 - 200	19 - 3/4	3.6 - .14	PA66	440 - 969	125 - 260	100 - 4
SB-BA-3/4-30M-PA12GF	30 - 100	19 - 3/4	3.6 - .14	PA12GF	1321 - 2911	100 - 212	100 - 4
SB-BA-3/4-60M-PA12GF	60 - 200	19 - 3/4	3.6 - .14	PA12GF	1321 - 2911	100 - 212	100 - 4
SB-BA-1-1/4-30M-PA12GF	30 - 100	32 - 1 1/4	4.7 - .19	PA12GF	2344 - 5166	100 - 212	200 - 8

*PA66 = Polyamide 66 [Nylon 66]; PA12 = Polyamide 12 [Nylon 12]; POM = Polyoxymethylene [Acetal]; PA12GF = Polyamide glass filled

**For very cold temperatures e.g. -40 C increase minimum diameter to 100 mm

For best results, Smart Band should be installed when product temperature is close to room temperature.

HCL Smart® Band Flex

SB-BA-FX-1/2-30M-POM - Glass fibre reinforced polymer (acetal) black uv resistant banding

Width: 12.7 mm (1/2"); Thickness 1.8 mm (.07"); Length: 30 M (100 ft);

Temperature Range: -40 C (-40F) to 95 C (200 F)

Break Strength: 2100 N (472 lb-ft); Retention Strength: 400 N (90 lb-ft)

Accessories:

Locking Head (buckle), uv resistant black acetal - HCL-SB-FX-BU-1/2-LH-POM

Manual Tensioning Tool – SM-FT-2000-13-FX





Smart® Band Buckles - Standard & Hybrid

Banding: Smart® Band, Smart® Band Hybrid

Tensioning tools: SM-FT-1000; SM-FT-2000; SM-FT-3000

Product #	Length mm - in	Width mm - in	Height mm - in	Material*	Max Temp C - F
SB-BU-1/4-ST-PA66	76 - 2.99	15 - .59	19.2 - .76	PA66	125 - 257
SB-BU-3/8-ST-PA12	77.2 - 3.04	22.9 - 0.9	21.5 - .85	PA12	105 - 221
SB-BU-3/8-ST-PA66	77.2 - 3.04	22.9 - 0.9	21.5 - .85	PA66	125 - 257
SB-BU-3/4-ST-PA66	63.8 - 2.51	22.9 - 0.9	28.3 - 1.11	PA66	125 - 257
SB-BU-3/4-HY-PA66	99.0 - 3.9	53.0 - 2.09	12.8 - .5	PA66	125 - 257
SB-BU-3/4-HY-POM	99.0 - 3.9	53.0 - 2.09	12.8 - .5	POM	95 - 203
SB-BU-3/4-HY-PA12GF	99.0 - 3.9	53.0 - 2.09	12.8 - .5	PA12GF	105 - 221
SB-BU-1-1/4-HY-PA12GF	135.5 - 5.33	76.8 - 3.02	16.8 - .66	PA12GF	105 - 221

* PA66 = Polyamide 66 [Nylon 66]; PA12 = Polyamide 12 [Nylon 12]; PA12GF = Polyamide glass filled; POM = Polyoxymethylene [Acetal]

				
SB-BU-1/4-ST	SB-BU-3/8-ST	SB-BU-3/4-ST	SB-BU-3/4-HY	SB-BU-1-1/4-HY

Smart® Band Compact Banding System

Glass-filled 32 mm [1 ¼"] wide band in specified lengths with new over-moulded compact buckle – adding over 10% to the performance of the Hybrid system
Suitable for heavy duty applications in subsea and subterranean environments
Tensioning tools: **SM-FT-1000-32; SM-FT-2000-32; SM-FT-3000-32**



Product #	Length* m - ft	Width mm - in	Thickness mm - in	Material**	Max Strength kgf - lbf	Max Temp C - F	Min Diameter mm - in
SB-COM-19-PA12GF	XXXX	19 - 3/4	4.7 - 0.19	PA12GF	91.8 - 202.25	100 - 212	
SB-COM-19-PPS	XXXX	19 - 3/4	4.7 - 0.19	PPS	91.8 - 202.25	175 - 347	
SB-COM-32-PA12GF-XXXX-MM	XXXX	32 - 1 1/4	4.7 - 0.19	PA12GF	2689 - 5929	100 - 212	250 - 10
SB-COM-32-PPS-XXXX-MM	XXXX	32 - 1 1/4	4.7 - 0.19	PPS	2068 - 5929	175 - 347	250 - 10
SB-COM-HL-32-PA12GF-XXXX-MM***	XXXX	32 - 1 1/4	4.7 - 0.19	PA12GF	tbd	100 - 212	250 - 10

* specify on order

**PA12GF = polyamide glass filled; PPS = Polyphenylene Sulfide

For best results, Smart Band Compact should be installed when product temperature is close to room temperature.

*** HL – denotes High Load – this product has an additional feature which enables it to be installed via Stingers/Rollers on Pipe-lay Vessels



Smart® Installation Tools

Product #	Type	Application	Buckle	Weight kg - lb
SM-FT-2000-13	Manual	Smart Band 7 mm (1/4"), 10 mm (3/8")	Std	.33 - .73
SM-FT-2000-19	Manual	Smart Band 19 mm (3/4"); Smart Tie 20 mm (3/4")	Std & Hybrid	.75 - 1.65
SM-FT-2000-32	Manual	Smart Band 32 mm (1 1/4"); Smart Tie 32 mm (1 1/4")	Hybrid & Compact	1.33 - 2.93
SM-FT-1000-19	Manual with Torque	Smart Band 19 mm (3/4")	Std & Hybrid	2.79 - 6.14
SM-FT-1000-20ST	Manual with Torque	Smart Tie 20 mm (3/4")	-	2.79 - 6.14
SM-FT-1000-32	Manual with Torque	Smart Band 32 mm (1 1/4")	Hybrid & Compact	2.79 - 6.14
SM-FT-1000-32ST	Manual with Torque	Smart Tie 32 mm (1 1/4")	-	2.79 - 6.14
SM-FT-3000-19	Pneumatic	Smart Band 19 mm (3/4")	Std & Hybrid	6.4 - 14.08
SM-FT-3000-20ST	Pneumatic	Smart Tie 20 mm (3/4")	-	6.4 - 14.08
SM-FT-3000-32	Pneumatic	Smart Band 32 mm (1 1/4")	Std & Hybrid	7.5 - 16.5
SM-FT-3000-32ST	Pneumatic	Smart Tie 32 mm (1 1/4")	-	7.5 - 16.5

SM-FT-2000-13	SM-FT-2000-19	SM-FT-2000-32	SM-FT-1000	SM-FT-3000

HCL Smart® Protector

Engineered polymer protector secures and guards cables in downhole applications

Part	Cable Configuration
SP100	1 x 1/4" control line 1 x 1/8" control line 1 x 2mm fibre optic
SP100-2	2 x 1/4" control line
SP-200	1 x 11mm sq. or rd encapsulated line
SP-300	1 or 2 x 11mm sq or rd encapsulated line; 1 or 2 x 1/4" control lines
SP-400-3820	Flat packs & flat esp cables up to 38mm w & 20mm h
SP-400-5228	Flat packs & flat esp cables up to 52mm w & 28mm h
SP-500-1721	Round cables 17mm – 21mm dia
SP-500-3338	Round cables 33mm – 38mm dia



Steel Strapping – Econo Packs

Steel strapping coil in self dispensing carton

Standard Duty Steel Strapping - .020" (.5 mm) thick

Carton dimensions 200 ft: 10.25" (260 mm) x 10.25" (260 mm) x 1.25" (32 mm)

Carton dimensions 300 ft: 12.5" (310 mm) x 12.5" (310 mm) x 1.25" (32 mm)



Product Number	Length Feet - m	Width inches - mm	Weight/Box lbs - kg	Break Strength lbs	Description
STS5020020	200 - 60	1/2 - 13	7.0 - 3.2	1180	Std duty
STS7520020	200 - 60	3/4 - 19	10.0 - 4.5	1765	Std duty
STS7520020HP	200 - 60	3/4 - 19	10.0 - 4.5	1255	Hole punched
STS5030020	300 - 90	1/2 - 13	10.0 - 4.5	1180	Std duty
STS7530020	300 - 90	3/4 - 19	15.0 - 6.8	1765	Std duty
STS7530020HP	300 - 90	3/4 - 19	15.0 - 6.8	1255	Hole punched

Steel Strapping – 100 lb. (45 kg) coils

Oscillating Coil (Osc)

Dimensions: 23" (590 mm) o.d. x 16" (410 mm) i.d. x 3.5" (90 mm) h

Skid lot: 12 coils

Ribbon Coil (Rib) dimensions: 26" (660 mm) o.d. x 16" (410 mm) i.d.

Skid lot: 24 coils



Product Number	Duty	Coil format	Width inches - mm	Thickness inches - mm	Length/coil ft - m	Break Strength lbs - kg
1003655	std	osc	1/2 - 13	.020 - .51	2942 - 896	1180 - 536
1007980	std	osc	3/4 - 19	.020 - .51	1961 - 597	1765 - 802
2014201	HT	rib	1 1/4 - 31	.031 - .79	759 - 231	5620 - 2554

Contact sales for other sizes

Seals



Open seals, standard duty: 1/2" - **1304105**, 3/4" - **1306105** in qty 50, 250, 1000, or bulk

Closed seals, standard duty: 1/2" - **1304446**, 3/4" - **1306250** in qty 50, 250, 1000, or bulk

Push Seals, Heavy Duty: 1 1/4" – **2300391** qty 1000

Thread-on seals Heavy Duty: 1 1/4" – **2301007** qty 1000

Other sizes and formats available



Tools for Steel Strapping

Manual Tensioning Tools

FWT2900

Manual Feedwheel Tensioner for steel strapping
3/8" – 3/4" W x .035" T



FWT3500

Heavy Duty Manual Feedwheel Tensioner for steel strapping
3/4" - 1 1/4" W x .035" T



RPT2270

Rack Pusher Tensioner for steel strapping
3/8" – 1 1/4" W x .031" T



RTS2230

Lever Handle Ratchet Wheel Tensioner with Cutter
1/4" – 3/4" W x (.015" - .025") T
(Scan QR code for demonstration video)



Manual Seal Notching Tools

NTC3124, NTC3126

Manual Seal Notching Tool for steel strapping
NTC3124 (1/2") or NTC3126 (3/4"), double notch down,
with 14" handles



NTC3173

Manual Seal Notching Tool for steel strapping
1 1/4" (.035"), single notch down, with 27" steel handles



Manual Strap Cutting Tools

SC1010

Light Duty Cutter with Spring Handle max 3/4" x .025"



SC2010

Medium Duty Cutter with 9" Handle max 1 1/4" x .035"



SC3060

Heavy Duty Cutter for HT steel strapping max 2" x .05"



Coil Dispenser Cart

Heavy Duty Dispenser Cart for Oscillating Wound Coils, with brake and tool box

100-5, standard with brake; **100-6** heavy duty with troller brake; **1000H** extra heavy duty; **1000P** for ribbon wound coils



Manual Seal-less Combination Tool

MSCT-19

Manual Seal-less Combination (tension & notch) for standard duty (SD) & high tensile (HT) steel strapping

3/4" (19 mm) x (.020" - .023")

Tool also available to fit strap width 1/2" (13 mm) or 5/8" (16 mm)



BAND-N-GO Inc.

Banding Together with Industry

8540 Keele Street, Unit 4, Concord ON L4K 2N2 CANADA

T: 888-871-6573; F: 905-669-1953

E: info@bandngo.com W: www.bandngo.com

Product Summary



Stainless Steel Banding,
Accessories & Tools



Stainless Steel Cable Ties
& Tools



Specialty Banding



Stainless & Galvanized
Steel Pre-formed Clamps



Plastic Cable Ties



Non Metallic
Banding & Tools



Steel Strapping, Seals
& Tools

Locally

